

4.1 Ubuntu Administration Commands

List of the most useful Ubuntu administration commands.

Package Management

List All Installed Packages

See exactly what is installed in your system,

```
dpkg --get-selections > installed-software.txt
```

The same list can also be used to install the same packages on another machine... **Note I have not tested this command myself yet.**

```
dpkg --set-selections < installed-software.txt
dselect
```

Determine Package Program Belongs To

Find out what packages if any use the specified folder,

```
dpkg -S "/etc/ssl/certs"
openssl, ca-certificates: /etc/ssl/certs
```

The package lookup will only work against the original binary. If it does not appear to work, check if the file you are referencing is actually a symbolic link and follow the links to the real binary file.

List all files relate to a package,

```
dpkg -L ca-certificates
/.
/etc
/etc/ssl
/etc/ssl/certs
/etc/ca-certificates
/etc/ca-certificates/update.d
/usr
/usr/sbin
/usr/sbin/update-ca-certificates
/usr/share
/usr/share/ca-certificates
...
```

Determine if package is installed,

```
dpkg -l | grep -i upstart
```

Service Management

Upstart

Upstart is moving towards being the official service management utility. So not all services are yet converted to upstart. However, for the ones that are, it is very easy to use.

I'm still filling this out.

Determine if a service is upstart based,

```
sudo status servicename
```

hmm... does not work with Apache2 so that is not yet managed by upstart but **sudo service apache2 status** works..... so I wonder if service is better.

See list of upstart jobs running,

```
ls /etc/init/*.conf  
http://askubuntu.com/questions/42444/the-list-of-running-daemons #possibly  
upstart way  
http://askubuntu.com/questions/42444/the-list-of-running-daemons
```

update-rc.d

Apache for example is not yet moved to upstart. So to manage it, use update-rc.d,

```
sudo update-rc.d apache2 disable
update-rc.d: warning: apache2 start runlevel arguments (none) do not match
LSB Default-Start values (2 3 4 5)
update-rc.d: warning: apache2 stop runlevel arguments (none) do not match
LSB Default-Stop values (0 1 6)
Disabling system startup links for /etc/init.d/apache2 ...
Removing any system startup links for /etc/init.d/apache2 ...
    /etc/rc0.d/K09apache2
    /etc/rc1.d/K09apache2
    /etc/rc2.d/S91apache2
    /etc/rc3.d/S91apache2
    /etc/rc4.d/S91apache2
    /etc/rc5.d/S91apache2
    /etc/rc6.d/K09apache2
Adding system startup for /etc/init.d/apache2 ...
    /etc/rc0.d/K09apache2 -> ../init.d/apache2
    /etc/rc1.d/K09apache2 -> ../init.d/apache2
    /etc/rc6.d/K09apache2 -> ../init.d/apache2
    /etc/rc2.d/K09apache2 -> ../init.d/apache2
    /etc/rc3.d/K09apache2 -> ../init.d/apache2
    /etc/rc4.d/K09apache2 -> ../init.d/apache2
    /etc/rc5.d/K09apache2 -> ../init.d/apache2
```

Don't just try and manually remove symlinks from init.d. Services will be enabled during package updates.

References

Start of good reading on upstart - <http://askubuntu.com/questions/19320/whats-the-recommend-way-to-enable-disable-services>

LSB (Linux Standard Base) way talks about legacy command and it's smart to figure it out - <http://askubuntu.com/questions/6358/how-do-you-restart-apache>